

Organica 592



Size

9½" x 60" nominal (23.8 cm x 151.5 cm)
8 mm thick

Waterproof Core

100% PVC-free, resin fused plant fiber
includes 66% plant based materials

Surface Effect

Embossed in register

Edge Treatment

Four-sided color-enhanced bevel

Installation

Click floating floor, angle-angle
(on, above, or below grade)

Compatible Acoustical Underlayments:

- Leggett & Platt® Whisper Step®
- Tred-MOR® dBarrier®

Attached Cushion

For superior sound abatement
and easier installation

Abrasion Class

AC5-heavy commercial traffic

Coordinating Moldings

See nextfloor.net for more details

Packaging

6 pieces per carton (30 lbs)
23.5 SF per carton
60 cartons per pallet
28 pallets per 40 HQ container

Testing

Castor Chair Test	ISO 4918	exceeds 75 000 Cycles
Critical Radiant Flux	ASTM E648	Class I
Surface Flammability	DOC FF 1-70	Passed
Coefficient of Friction	ASTM 2047	0.95
Static Load Limit	ASTM F970	exceeds 3000 lbs
Sound Transmission Class (STC)	ASTM E90	63
Impact Insulation Class (IIC)	ASTM E492	68
High Frequency Impact Insulation Class(HIIC)	ASTM E3222	90
FloorScore Certified		

Warranties

Lifetime Waterproof
Lifetime Residential Wear
Chair protectors NOT required under chairs with roller casters
10-Year Residential Scratch Resistance
10-Year Residential Pet Scratch Resistance
10-Year Residential Stain Resistance
Lifetime No Cupping*
20-Year Commercial Wear

*When properly installed, see full warranty text at nextfloor.net



Sample SKUs

Handle Boards

HB592NF
5 per carton (65 lbs)

Strap Sets

SS592NF
5 per carton (44 lbs)

Step Up Display

8CARDS592NF-1
(592 004, 006, 051, 052)
8CARDS592NF-2
(592 012, 015, 021, 054)
FIXT592NF with DEMOKIT
PL592NF
Packaged in 4 cartons (125.2 lbs)

Wing Rack Update

WING8CARDS592NF-1
(592 004, 006, 051, 052)
WING8CARDS592NF-2
(592 012, 015, 021, 054)
Packaged in 2 cartons (37 lbs)

Step Up Display Conversion Kit

Lighthouse Point to Organica
8CARDS592NF-1
(592 004, 006, 051, 052)
8CARDS592NF-2
(592 012, 015, 021, 054)
PL592NF
DEMO592NF
Packaged in 4 cartons (81.2 lbs)