

PLATINUM



PERFORMANCE
ACCESSORIES

The perfect finish for any floor.

PLATINUM Underlayment for LVF



Platinum underlayment for LVF is easy to install. The fanfold design is lightweight, lays flat, cuts easily and requires no acclimation time.

- For use with floating vinyl floors
- Supports the floor's locking system
- Superior sound control

THICKNESS
1.5mm

MOISTURE PROTECTION
0.01 lbs - 24 h - 1,000 sq ft

THERMAL INSULATION
R-Value 0.39 (6.6 per inch)

COMPRESSION STRENGTH
> 65 PSI

SIZE
100 sq ft - 3.9' x 25.7'

IMPACT SOUND INSULATION
IIC -72 - STC 66 - Delta 26

SMOOTHING
1.0mm

SAFETY
Odorless, non-toxic

A64294

Installation Instructions:

1. Ensure the floor is clean and dry before installing underlayment.
2. Starting in a corner, install the first row of underlayment with moisture barrier facing upward. Install the underlayment to the wall and trim around any obstacles.
3. Align the second row of underlayment to the first row ensuring there are no gaps or overlapping seams. Seal with underlayment tape (not included).
4. Repeat this process until the entire floor is covered.
5. Install the flooring per the manufacturer's instructions.

Instrucciones de instalación:

1. Asegúrese de que el piso esté limpio y seco antes de instalar el contrapiso.
2. Comenzando en una esquina, instale la primera hilera de contrapiso con la barrera contra humedad hacia arriba. Instale el contrapiso en la pared y recorte alrededor de cualquier obstáculo.
3. Alinee la segunda hilera de contrapiso con la primera asegurándose de que no queden espacios ni que las uniones se superpongan. Selle con la cinta de contrapiso. (no se incluye)
4. Repita este proceso hasta que todo el piso esté cubierto.
5. Instale el piso de acuerdo con las instrucciones del fabricante.